



*P***FLUEGER**[®]
THE SMART CHOICE[™]

2017 | Product Guide



PFLUEGER[®]
THE SMART CHOICE[™]

At Pflueger we pride ourselves on creating the 'smartest' reels and combos on the market. Pflueger products are of the highest quality with the most features at the best possible price. Pflueger is built on an incredibly rich history that is a story of passion, hard work, perseverance, and cutting edge innovation. Join us as we continue to innovate the sport that we all hold close to our hearts. Take pride in knowing that in every Pflueger you add to your collection that you are getting more than what you paid for. So relax, enjoy, and know that we have taken into account even the smallest of details to deliver excellence as we have done since 1881.

TABLE OF CONTENTS

PATRIARCH XT SP	2
PATRIARCH SP	3
SUPREME XT SP	4
SUPREME SP	4
PURIST SP	5
ARBOR SP	5
PRESIDENT XT SP	6
PRESIDENT SP	7
PRESIDENT SP COMBO.....	7
TRION SP	8
TRION SP COMBO.....	8
MONARCH SP COMBO.....	9
PATRIARCH XT LP.....	10
PATRIARCH LP	10
SUPREME XT LP.....	11
SUPREME LP	11
PRESIDENT XT LP.....	12
PRESIDENT LP	13
TRION LP	14
TRION LP COMBO	14
MONARCH LP COMBO	15
PRESIDENT SC.....	16
TRION SC	16
PRESIDENT SC COMBO	17
TRION SC COMBO.....	17
IRONHAWK.....	18
NIGHTHAWK.....	19
LADY PRESIDENT	20
LADY TRION SP COMBO.....	20
LADY TRION LP COMBO	21
PATRIARCH FLY REEL.....	22
PRESIDENT FLY REEL.....	23
MEDALIST FLY REEL.....	23
MONARCH FLY REEL.....	24
AUTOMATIC FLY REEL	24
COMPLETE FLY OUTFITS	25



Patriarch^{XT}

NEW



11 Bearing System



XCR Ball Bearings

Pflueger's highest performance, shielded, & friction reducing bearings



Magnesium Body & Rotor

Featherlight design



SMARTgear Technology

Durability and precision you can feel



SMARTretrieve Technology

Precision line lay for optimal line performance



Sealed Carbon Drag

Sealed system, always lubricated, always smooth



Carbon Handle

21% lighter than aluminum



Titanium Main Shaft

Reduces weight & improves performance



Model #
PARXTSP30X
PARXTSP35X

SAP #
1383416
1383417

Capacity: Mono
120 yards / 6 lb.
140 yards / 8 lb.

Capacity: Braid
115 yards / 8 lb.
150 yards / 10 lb.

Max Drag lb
10
14

Gear Ratio
6.2:1
6.2:1

Inches-Per-Turn
32
34

Weight oz
6.2
7.2

Patriarch™

NEW



10 Bearing System



XCR Ball Bearings

Pflueger's highest performance, shielded, & friction reducing bearings



Magnesium Body & Rotor

Featherlight design



SMARTgear Technology

Durability and precision you can feel



SMARTretrieve Technology

Precision line lay for optimal line performance



Sealed Carbon Drag

Sealed system, always lubricated, always smooth



Carbon Handle

21% lighter than aluminum



Titanium Main Shaft

Reduces weight & improves performance



Model #	SAP #	Capacity: Mono	Capacity: Braid	Max Drag lb	Gear Ratio	Inches-Per-Turn	Weight oz
PARSP25X	1383418	110 yards / 4 lb.	110 yards / 6 lb.	5	5.2:1	24.5	5.3
PARSP30X	1383419	120 yards / 6 lb.	115 yards / 8 lb.	10	5.2:1	27	6.2
PARSP35X	1383420	140 yards / 8 lb.	150 yards / 10 lb.	14	5.2:1	28.8	7.3



Supreme^{XT}



10 Bearing System



Magnesium Body & Rotor

Feather light design



Braid Ready Spool

Allows braid to be tied directly to spool



Sealed Carbon Drag

Sealed system, always lubricated, always smooth



Carbon Handle

21% lighter than aluminum



EVA Knob

High density EVA, lightweight comfort



SMARTretrieve Technology

Precision line lay for optimal line performance



Model #	SAP #	Capacity: Mono	Capacity: Braid	Max Drag lb	Gear Ratio	Inches-Per-Turn	Weight oz
SUPXTSP25X	1323780	110 yards / 4 lb.	140 yards / 6 lb.	8	5.2:1	22.8	6.0
SUPXTSP30X	1323781	145 yards / 6 lb.	190 yards / 8 lb.	10	6.2:1	31.8	6.8
SUPXTSP35X	1323782	185 yards / 8 lb.	220 yards / 10 lb.	12	6.2:1	33.8	8.0
SUPXTSP40X	1323783	230 yards / 10 lb.	280 yards / 14 lb.	14	6.2:1	38.6	8.7

Supreme



9 Bearing System



Magnesium Body & Rotor

Feather light design



Braid Ready Spool

Allows braid to be tied directly to spool



Stainless Steel/Oil Felt Drag

Consistent drag pressure, & corrosion resistant



Aluminum Handle

Aircraft grade aluminum handle, extreme durability



Soft Touch Knob

Soft touch rubber knob provides excellent grip & comfort



SMARTretrieve Technology

Precision line lay for optimal line performance



Model #	SAP #	Capacity: Mono	Capacity: Braid	Max Drag lb	Gear Ratio	Inches-Per-Turn	Weight oz
SUPSP25X	1323784	110 yards / 4 lb.	140 yards / 6 lb.	8	5.2:1	22.8	6.6
SUPSP30X	1323785	145 yards / 6 lb.	190 yards / 8 lb.	10	6.2:1	31.8	7.5
SUPSP35X	1323786	185 yards / 8 lb.	220 yards / 10 lb.	12	6.2:1	33.8	8.8
SUPSP40X	1323787	230 yards / 10 lb.	280 yards / 14 lb.	14	6.2:1	38.6	9.6

Purist®



10 Bearing System



Hybrid Body

Aluminum body with a graphite body cover, lightweight strength



Aluminum Spool

Lightweight, durable, spool design



Sealed Carbon Drag

Sealed system, always lubricated, always smooth



Aluminum Handle

Aircraft grade aluminum handle, extreme durability



Soft Touch Knob

Soft touch rubber knob provides excellent grip & comfort



Aluminum Bail

Thick aluminum bail wire design, rigid to prevent mis-shaping



Model #	SAP #	Capacity: Mono	Capacity: Braid	Max Drag lb	Gear Ratio	Inches-Per-Turn	Weight oz
1325X	1265678	115 yards / 4 lb.	135 yards / 6 lb.	6	5.2:1	22.4	7.3
1330X	1265679	115 yards / 6 lb.	180 yards / 8 lb.	9	5.2:1	25.2	8.6
1335X	1265680	145 yards / 8 lb.	205 yards / 10 lb.	10	5.2:1	27.4	10.3
1340X	1265681	195 yards / 10 lb.	260 yards / 14 lb.	12	5.2:1	30.2	11.3

RT CHOICE™ Arbor



8 Bearing System



Hybrid Body

Aluminum body with a graphite body cover, lightweight strength



Aluminum Spool

Lightweight, durable, spool design



Sealed Carbon Drag

Sealed system, always lubricated, always smooth



Aluminum Handle

Aircraft grade aluminum handle, extreme durability



Soft Touch Knob

Soft touch rubber knob provides excellent grip & comfort



Large Arbor

Large arbor reel increases casting distance & minimizes line twist



Model #	SAP #	Capacity: Mono	Capacity: Braid	Max Drag lb	Gear Ratio	Inches-Per-Turn	Weight oz
7430X	1197159	120 yards / 6 lb.	160 yards / 8 lb.	10	4.3:1	25	8.5
7435X	1204765	155 yards / 8 lb.	195 yards / 10 lb.	10	4.3:1	26.6	8.8
7440X	1197160	150 yards / 10 lb.	250 yards / 15 lb.	18	4.3:1	29.7	11.2



President^{XT}

NEW

10 Bearing System *

Aluminum Main Shaft
30% lighter than stainless steel

Braid Ready Spool
Allows braid to be tied directly to spool

Sealed Drag
Sealed system, always lubricated, always smooth

Carbon Handle
21% lighter than aluminum

Rubber Cork Knob
Rubber & cork material provides exceptional grip in all conditions

* PRESXTSP20X is a 7 Bearing System



Model #	SAP #	Capacity: Mono	Capacity: Braid	Max Drag lb	Gear Ratio	Inches-Per-Turn	Weight oz
PRESXTSP20X*	1383421	100 yards / 4 lb.	125 yards / 6 lb.	6	5.2:1	20.7	5.6
PRESXTSP25X	1383422	110 yards / 4 lb.	140 yards / 6 lb.	8	5.2:1	22.4	6.6
PRESXTSP30X	1383423	145 yards / 6 lb.	190 yards / 8 lb.	10	6.2:1	31	7.6
PRESXTSP35X	1383424	185 yards / 8 lb.	220 yards / 10 lb.	12	6.2:1	35	9.1
PRESXTSP40X	1383425	230 yards / 10 lb.	280 yards / 14 lb.	14	6.2:1	38	10.1

President®



10 Bearing System*



Graphite Body & Rotor

Lightweight graphite reel construction



Braid Ready Spool

Allows braid to be tied directly to spool



Stainless Steel/Oil Felt Drag

Consistent drag pressure, & corrosion resistant



Aluminum Handle

Aircraft grade aluminum handle, extreme durability



Soft Touch Knob

Soft touch rubber knob provides excellent grip & comfort



Aluminum Bail

Thick aluminum bail wire design, rigid to prevent mis-shaping

* 6920 is a 7 Bearing System



Model #	SAP #	Capacity: Mono	Capacity: Braid	Max Drag lb	Gear Ratio	Inches-Per-Turn	Weight oz
6920*	1236618 Box / 1236649 Clam	100 yards / 4 lb.	125 yards / 6 lb.	6	5.2:1	20.7	5.9
6925	1236650 Box / 1236651 Clam	110 yards / 4 lb.	140 yards / 6 lb.	6	5.2:1	22.4	7.2
6930	1236652 Box / 1236653 Clam	145 yards / 6 lb.	190 yards / 8 lb.	9	5.2:1	25.2	8.3
6935	1236654 Box / 1236655 Clam	185 yards / 8 lb.	220 yards / 10 lb.	10	5.2:1	27.4	9.9
6940	1236656 Box / 1236640 Clam	230 yards / 10 lb.	280 yards / 14 lb.	12	5.2:1	30.2	10.9

President®



10 Bearing System



Braid Ready Spool

Braid ready aluminum spool



Aluminum Handle

Aircraft grade aluminum handle, extreme durability



IM-8 Graphite

Lightweight & durable graphite rod performance



Stainless Steel Guides

Strong & corrosion resistant guide system

Model #	SAP #	Power	Length	Pieces	Lure Weight	Reel	Capacity: Mono
PFLPRES2-482COMBO	1236667	Ultra Light	4'8"	2	1/32-3/16	20*	100 yards / 4 lb.
PFLPRES2-50COMBO	1236668	Ultra Light	5'	1	1/32-3/16	25	110 yards / 4 lb.
PFLPRES2-56COMBO	1236669	Light	5'6"	1	1/16-3/8	30	145 yards / 6 lb.
PFLPRES2-60COMBO	1236670	Medium	6'	1	1/8-5/8	30	145 yards / 6 lb.
PFLPRES2-66COMBO	1236671	Medium	6'6"	1	1/8-5/8	35	185 yards / 8 lb.
PFLPRES2-662MCOMBO	1257406	Medium	6'6"	2	1/8-5/8	35	185 yards / 8 lb.
PFLPRES2-662LCOMBO	1236672	Light	6'6"	2	1/16-3/8	25	185 yards / 8 lb.
PFLPRES2-70COMBO	1236673	Medium	7'	1	1/8-5/8	40	230 yards / 10 lb.



Trion®


7 Bearing System *

Graphite Body & Rotor
 Lightweight graphite reel construction

Aluminum Spool
 Lightweight, durable, spool design

Stainless Steel/Oil Felt Drag
 Consistent drag pressure, & corrosion resistant

Aluminum Handle
 Aircraft grade aluminum handle, extreme durability

Soft Touch Knob
 Soft touch rubber knob provides excellent grip & comfort

*TRI20 is a 5 Bearing System



Model #	SAP #	Capacity: Mono	Capacity: Braid	Max Drag lb	Gear Ratio	Inches-Per-Turn	Weight oz
TRI20*	1292357 Box / 1292358 Clam	100 yards / 4 lb.	125 yards / 6 lb.	6	5.2:1	20.7	5.9
TRI25	1292369 Box / 1292370 Clam	110 yards / 4 lb.	140 yards / 6 lb.	8	5.2:1	22.4	7.1
TRI30	1292371 Box / 1292372 Clam	145 yards / 6 lb.	190 yards / 8 lb.	10	5.2:1	25.2	8.6
TRI35	1292373 Box / 1292374 Clam	185 yards / 8 lb.	220 yards / 10 lb.	12	5.2:1	27.4	10.4
TRI40	1292375 Box / 1292376 Clam	230 yards / 10 lb.	280 yards / 14 lb.	16	5.2:1	30.2	11.4

Trion®

THE SMART CHOICE™


7 Bearing System *
 Corrosion resistant stainless steel bearings

Aluminum Spool
 Lightweight, durable, spool design

Aluminum Handle
 Aircraft grade aluminum handle, extreme durability

IM-6 Graphite
 Lightweight & durable graphite rod performance

Stainless Steel Guides
 Strong & corrosion resistant guide system

*TRI20 is a 5 Bearing System



Model #	SAP #	Power	Length	Pieces	Lure Weight	Reel	Capacity: Mono
TRISP5020ULCBO	1292377	Ultra Light	5'	1	1/32-3/16	20*	100 yards / 4 lb.
TRISP5625LCBO	1292378	Light	5'6"	1	1/16-3/8	25	110 yards / 4 lb.
TRISP6030MLCBO	1292379	Medium Light	6'	1	1/16-1/4	30	145 yards / 6 lb.
TRISP6635MCBO	1292380	Medium	6'6"	1	1/8-5/8	35	220 yards / 10 lb.
TRISP6635M2CBO	1292381	Medium	6'6"	2	1/8-5/8	35	185 yards / 8 lb.
TRISP6625L2CB	1292383	Light	6'6"	2	1/16-3/8	25	145 yards / 6 lb.
TRISP7040MCBO	1292382	Medium	7'	1	1/8-5/8	40	230 yards / 10 lb.

PELAGER®

Monarch™

SMART CHOICE™



5 Bearing System



Graphite Body & Rotor

Lightweight graphite reel construction



Aluminum Bail

Thick aluminum bail wire design, rigid to prevent mis-shaping



IM-6 Graphite

Mid-modulus graphite blank construction, lightweight sensitivity



Stainless Steel Guides

Strong & corrosion resistant guide system



Model #	SAP #	Power	Length	Pieces	Lure Weight	Reel	Capacity: Mono
MONSP6030ML2CBO	1371151	Medium Light	6'	2	1/16-1/4	30	140 yards / 6 lb.
MONSP6630M2CBO	1371152	Medium	6'6"	2	1/8-5/8	30	140 yards / 6 lb.
MONSP7035M2CBO	1371153	Medium	7'	2	1/8-5/8	35	210 yards / 10 lb.
MONSP5620UL2CBO	1371154	Ultra Light	5'6"	2	1/16-3/8	20	110 yards / 4 lb.
MONSP6625L2CBO	1371155	Light	6'6"	2	1/16-3/8	25	120 yards / 4 lb.
MONSP7025UL2CBO	1371156	Ultra Light	7'	2	1/16-3/8	25	120 yards / 4 lb.











Patriarch™^{XT}

- **11 Bearing System**
- **C45 Carbon Sideplate**
45% carbon fiber sideplate material, lightweight durability
- **Ultimate Braking System**
6-pin centrifugal & magnetic brake
- **C-Lock Sideplate System**
Cam locking sideplate allows for quick breaking adjustments
- **Aluminum Frame**
Ensures precise gear alignment
- **Sealed Carbon Drag**
Sealed system, always lubricated , always smooth
- **Carbon Handle**
21% lighter than aluminum
- **EVA Knob**
High density EVA, lightweight comfort




Model #	SAP #	Capacity: Mono	Capacity: Braid	Max Drag lb	Gear Ratio	Inches-Per-Turn	Weight oz
PATXT64LPX	1323788	145 yards / 12 lb.	140 yards / 30 lb.	20	6.4:1	26	5.8

Patriarch™

- **11 Bearing System**
- **C45 Carbon Sideplate**
45% carbon fiber sideplate material, lightweight durability
- **Ultimate Braking System**
6-pin centrifugal & magnetic brake
- **C-Lock Sideplate System**
Cam locking sideplate allows for quick breaking adjustments
- **Aluminum Frame**
Ensures precise gear alignmen
- **Sealed Carbon Drag**
Sealed system, always lubricated always smooth
- **Carbon Handle**
21% lighter than aluminum
- **EVA Knob**
High density EVA, lightweight comfort



	Model #	SAP #	Capacity: Mono	Capacity: Braid	Max Drag lb	Gear Ratio	Inches-Per-Turn	Weight oz
	PAT71LPX	1294124	145 yards / 12 lb.	140 yards / 30 lb.	20	7.1:1	29	6.3
	PAT71LHPX	1294126	145 yards / 12 lb.	140 yards / 30 lb.	20	7.1:1	29	6.3
	PAT79LPX	1294125	145 yards / 12 lb.	140 yards / 30 lb.	20	7.9:1	32	6.3

Supreme^{XT}



10 Bearing System



C45 Carbon Sideplate

45% carbon fiber sideplate material, lightweight durability



Centrifugal Braking System

Adjustable brake controls speed & backlash



C-Lock Sideplate System

Cam locking sideplate allows for quick breaking adjustments



Aluminum Frame

Ensures precise gear alignment



Sealed Carbon Drag

Sealed system, always lubricated always smooth



EVA Knob

High density EVA, lightweight comfort



Model #	SAP #	Capacity: Mono	Capacity: Braid	Max Drag lb	Gear Ratio	Inches-Per-Turn	Weight oz
SUPXT64LPX	1294127	145 yards / 12 lb.	140 yards / 30 lb.	20	6.4:1	26	6.5
SUPXT71LPX	1294128	145 yards / 12 lb.	140 yards / 30 lb.	20	7.1:1	29	6.5
SUPXT71LHLPX	1294169	145 yards / 12 lb.	140 yards / 30 lb.	20	7.1:1	29	6.5

Supreme^{RT}



9 Bearing System



Aluminum Frame

Ensures precise gear alignment, maintaining gear feel & smoothness



Magnetic Braking System

Externally adjustable magnetic brake



Aluminum Handle

Aircraft grade aluminum handle, extreme durability



Soft Touch Knob

Soft touch rubber knob provides excellent grip & comfort



Model #	SAP #	Capacity: Mono	Capacity: Braid	Max Drag lb	Gear Ratio	Inches-Per-Turn	Weight oz
SUP54LPX	1294170	145 yards / 12 lb.	140 yards / 30 lb.	20	5.4:1	22	7.8
SUP64LPX	1294171	145 yards / 12 lb.	140 yards / 30 lb.	20	6.4:1	26	7.8
SUP64LHLPX	1294173	145 yards / 12 lb.	140 yards / 30 lb.	20	6.4:1	26	7.8
SUP71LPX	1294172	145 yards / 12 lb.	140 yards / 30 lb.	20	7.1:1	29	7.8



President^{XT}®

NEW



9 Bearing System



C30 Carbon Sideplate

30% carbon material,
lightweight durability



Magnetic Braking System

Externally adjustable brake
controls speed & backlash



Aluminum Handle

Aircraft grade aluminum,
extreme durability



Rubber Cork Knob

Rubber & cork material provides
exceptional grip in all conditions



Model #
PRESXT73LP

SAP #
1383404 Box / 1383405 Clam

Capacity: Mono
145 yards / 12 lb.

Capacity: Braid
140 yards / 30 lb.

Max Drag lb
12

Gear Ratio
7.3:1

Inches-Per-Turn
31

Weight oz
7.7

President®

NEW



7 Bearing System



Graphite Frame & Sideplate

Lightweight graphite reel construction



Magnetic Braking System

Externally adjustable brake controls speed & backlash



Aluminum Handle

Aircraft grade aluminum, extreme durability



Model #
PRES73LP

SAP #
1383406 Box / 1383407 Clam

Capacity: Mono
145 yards / 12 lb.

Capacity: Braid
140 yards / 30 lb.

Max Drag lb
12





Gear Ratio
7.3:1

Inches-Per-Turn
31

Weight oz
7.9








Trion® NEW

-  **6 Bearing System**
-  **Graphite Frame & Sideplate**
Lightweight graphite reel construction
-  **Magnetic Braking System**
Externally adjustable brake controls speed & backlash
-  **Aluminum Handle**
Aircraft grade aluminum, extreme durability



Model #	SAP #	Capacity: Mono	Capacity: Braid	Max Drag lb	Gear Ratio	Inches-Per-Turn	Weight oz
TRI73LP	1383408 Box / 1383409 Clam	145 yards / 12 lb.	140 yards / 30 lb.	12	7.3:1	31	7.8

Trion® NEW






-  **6 Bearing System**
Corrosion resistant stainless steel bearings
-  **Magnetic Braking System**
Externally adjustable brake controls spool rotation & backlash
-  **Aluminum Handle**
Aircraft grade aluminum handle, extreme durability
-  **IM-6 Graphite**
Lightweight & durable graphite rod performance
-  **Stainless Steel Guides**
Strong & corrosion resistant guide system



Model #	SAP #	Power	Length	Pieces	Lure Weight	Reel	Capacity: Mono
TRILP70MHCBO	1383411	Medium Heavy	7'	1	1/4-3/4	LP	145 yard / 12 lb.



Monarch™ **NEW**

-  **5 Bearing System**
Corrosion resistant stainless steel bearings
-  **Magnetic Braking System**
Externally adjustable brake controls spool rotation & backlash
-  **Aluminum Handle**
Aircraft grade aluminum handle, extreme durability
-  **IM-6 Graphite**
Lightweight & durable graphite rod performance
-  **Stainless Steel Guides**
Strong & corrosion resistant guide system

Model #
MONLP70MHCBO

SAP #
1383412

Power
Medium Heavy

Length
7'

Pieces
1

Lure Weight
1/4-3/4

Reel
LP

Capacity: Mono
145 yard / 12 lb.



President®



5 Bearing System



Aluminum Frame
Ensures precise gear alignment



Aluminum Cone
Highest quality machined aluminum front cone design



Dual Titanium Pins*
Easier line pick-up with high-grade, wear resistant materials



Aluminum Handle
Aircraft grade aluminum handle, extreme durability



Soft Touch Knob
Soft touch rubber knob provides excellent grip & comfort



* MC and MS have single pick-up pins

Model #	SAP #	Capacity: Mono	Max Drag lb	Gear Ratio	Inches-Per-Turn	Weight oz
PRES6USCX	1299700	90 yards / 6 lb.	6	3.4:1	14.5	8.6
PRES6SCX	1294316	90 yards / 6 lb.	6	3.4:1	14.5	9.0
PRES10SCX	1294315	75 yards / 10 lb.	10	3.8:1	18.5	11.2
PRES10SCB	1319325	75 yards / 10 lb.	10	3.8:1	18.5	11.2

Trion®



2 Bearing System



Aluminum Frame
Ensures precise gear alignment



Aluminum Cone
Highest quality machined aluminum front cone design



Dual Titanium Pins*
Easier line pick-up with high-grade, wear resistant materials



Soft Touch Knob
Soft touch rubber knob provides excellent grip & comfort



* MC and MS have single pick-up pins



Model #	SAP #	Capacity: Mono	Max Drag lb	Gear Ratio	Inches-Per-Turn	Weight oz
TRIMCSCB	1294304	70 yards / 4 lb.	6	4.1:1	14	5.5
TRIMSSCB	1294306	70 yards / 4 lb.	6	4.1:1	14	5.2
TRI6SCB	1294301	90 yards / 6 lb.	6	3.4:1	14.5	6.4
TRI6USCB	1294302	90 yards / 6 lb.	6	3.4:1	14.5	6.4
TRI10SCB	1294299	75 yards / 10 lb.	10	3.8:1	18.5	10.0
TRI10USCB	1294300	75 yards / 10 lb.	10	3.8:1	18.5	10.0



President™

- 5 Bearing System**
Corrosion resistant stainless steel bearings
- Aluminum Frame**
Ensures precise gear alignment
- Aluminum Cone**
Highest quality machined aluminum front cone design
- IM-8 Graphite**
Lightweight & durable graphite rod performance
- Stainless Steel Guides**
Strong & corrosion resistant guide system

Model #
PRESSC606L2CB0
PRESSC6610M2CB0

SAP #
1294318
1294317

Power
Light
Medium

Length
6'
6'6"

Pieces
2
2

Lure Weight
1/16-3/8
1/8-5/8

Reel
6
10

Capacity: Mono
90 yards / 6 lb.
75 yards / 10 lb.



IRON HAWK®



HIDDEN HANDLE
DESIGN

TAC
HANDLE®

3 Year
Limited
WARRANTY



6 Bearing System



Magnetic Braking System

Externally adjustable brake controls
spool rotation & backlash



EVA Knob

High density EVA, lightweight
comfort

Model #
IRHLP70MHFCB0

SAP #
1323794

Power
Medium Heavy

Length
7'

Pieces
1

Lure Weight
1/4-1/2

Reel
LP

Capacity: Mono
110 yards / 14 lb.

IRON HAWK®



HIDDEN HANDLE
DESIGN

TAC
HANDLE®

3 Year
Limited
WARRANTY



7 Bearing System



Braid Ready Spool

Braid ready aluminum spool



EVA Knob

High density EVA, lightweight
comfort



Model #
IRHSP6930MFCB0

SAP #
1323793

Power
Medium

Length
6'9"

Pieces
1

Lure Weight
1/8-5/8

Reel
30

Capacity: Mono
145 yards / 6 lb.

NIGHTHAWK™



SS GUIDES

TAC
HANDLE3 Year
Limited
WARRANTY**5 Bearing System**

Corrosion resistant stainless steel bearings

**Magnetic Braking System**

Externally adjustable brake controls spool rotation & backlash

**Soft Touch Knob**

Soft touch knob provides excellent grip & comfort

Model #
NIHLP70MHFCBOSAP #
1323796Power
Medium HeavyLength
7'Pieces
1Lure Weight
1/4-1/2Reel
LPCapacity: Mono
110 yards / 14 lb.THE SMART CHOICE™
NIGHTHAWK™

SS GUIDES

TAC
HANDLE3 Year
Limited
WARRANTY**5 Bearing System**

Corrosion resistant stainless steel bearings

**Braid Ready Spool**

Braid ready aluminum spool

**Aluminum Handle**

Aircraft grade aluminum handle, extreme durability

Model #
NIHSP6930MFCBO
NIHSP6930MF2CBOSAP #
1323795
1344017Power
Medium
MediumLength
6'9"
6'9"Pieces
1
2Lure Weight
1/8-5/8
1/8-5/8Reel
30
30Capacity: Mono
145 yards / 6 lb.
145 yards / 6 lb.

President®


10 Bearing System

Graphite Body & Rotor
 Lightweight graphite reel construction

Braid Ready Spool

Allows braid to be tied directly to spool


Stainless Steel/Oil Felt Drag
 Consistent drag pressure, & corrosion resistant

Aluminum Handle

Aircraft grade aluminum handle, extreme durability


Soft Touch Knob

Soft touch rubber knob provides excellent grip & comfort


Aluminum Bail

Thick aluminum bail wire design, rigid to prevent mis-shaping



Model #	SAP #	Capacity: Mono	Capacity: Braid	Max Drag lb	Gear Ratio	Inches-Per-Turn	Weight oz
6925L	1315310 Box/Clam	110 yards / 4 lb.	140 yards / 6 lb.	6	5.2:1	22.4	7.2
6930L	1315311 Box/Clam	145 yards / 6 lb.	190 yards / 8 lb.	9	5.2:1	25.2	8.3
6935L	1315312 Box/Clam	185 yards / 8 lb.	220 yards / 10 lb.	10	5.2:1	27.4	9.9
6940L	1315313 Box/Clam	230 yards / 10 lb.	280 yards / 14 lb.	12	5.2:1	30.2	10.9

Lady Trion™


7 Bearing System

Corrosion resistant stainless steel bearings


Aluminum Spool

Lightweight, durable, spool design


Aluminum Handle

Aircraft grade aluminum handle, extreme durability


IM-6 Graphite

Lightweight & durable graphite rod performance


Stainless Steel Guides

Strong & corrosion resistant guide system



Model #	SAP #	Power	Length	Pieces	Lure Weight	Reel	Capacity: Mono
TRISPL5020ULCB0	1293247	Ultra Light	5'	1	1/32-3/16	20	100 yards / 4 lb.
TRISPL6630M2CB0	1293245	Medium	6'6"	2	1/8-5/8	30	145 yards / 6 lb.
TRISPL61035MCB0	1293246	Medium	6'10"	1	1/8-5/8	35	185 yards / 8 lb.

WEGGAR®

RT CHOICE™ LadyTrion™



4 Bearing System

Corrosion resistant stainless steel bearings



Magnetic Braking System

Externally adjustable brake controls spool rotation & backlash



Aluminum Handle

Aircraft grade aluminum handle, extreme durability



IM-6 Graphite

Lightweight & durable graphite rod performance



Stainless Steel Guides

Strong & corrosion resistant guide system



Model #
TRILPL63MCB0

SAP #
1294314

Power
Medium

Length
6'3"

Pieces
1

Lure Weight
1/8-5/8

Reel
LP

Capacity: Mono
150 yards / 12 lb.



Patriarch™



Machined Aluminum
High grade, precision machined frame and spool



Large Arbor
Maximum line retrieval, less line coiling



Sealed Disk Drag
Waterproof disc drag mechanism



Aluminum Handle
Ergonomic aluminum handle



All Water Design
Freshwater and saltwater safe



Left/Right hand Retrieve
Convertible retrieve



Quick Release
Quick release spool



Model	SAP	Capacity	Weight(oz)	Diameter
PAT34X	1370763	WF3+55	4.8	3.31"
PAT56X	1370764	WF5+65	5.3	3.74"
PAT78X	1370765	WF7+90	5.5	3.94"
PAT910X	1370766	WF10+180	8.5	4.29"
PAT1112X	1370767	WF11+230	8.8	4.61"

President®

NEW

Machined Aluminum
High grade, precision machined frame and spool

Mid Arbor
Increased line retrieval and balance

Disk Drag
Smooth stacked disc drag mechanism

Aluminum Handle
Ergonomic aluminum handle

Left/Right hand Retrieve
Convertible retrieve

Quick Release
Quick release spool

Reel Pouch
Protective reel pouch included


Model	SAP	Capacity	Weight(oz)	Diameter
PRES34X	1398028	WF3+55	4.3	3
PRES56X	1398029	WF5+65	4.6	3.25
PRES78X	1398030	WF7+90	4.8	3.5
PRES910X	1398031	WF10+120	4.9	3.75
PRES112X	1398032	WF12+250	7.2	4.13

MEDALIST

TRADE MARK


Machined Aluminum
High grade, precision machined frame and spool

Standard Arbor
High backing capacity spool

Click & Pawl
Precision click check mechanism

Polymer Handle
Classic lightweight durability

Left/Right hand Retrieve
Convertible retrieve

Quick Release
Quick release spool

Reel Pouch
Protective reel pouch included


Model	SAP	Capacity	Weight(oz)	Diameter
MED34X	1370768	WF3+75	4.6	2.87"
MED56X	1370769	WF5+125	5.4	3.19"
MED78X	1370770	WF7+250	7.6	3.86"



Monarch™

- 

Die Cast Aluminum
Lightweight, cast aluminum for strength and durability
- 

Standard Arbor
High backing capacity spool
- 

Disk Drag*
Smooth stacked disk drag mechanism
- 

Polymer Handle
Classic lightweight durability
- 

Left/Right hand Retrieve
Convertible retrieve
- 

Quick Release
Quick release spool



* MON 3/4 has a click & pawl drag

Model	SAP	Capacity	Weight(oz)	Diameter
MON34X	1370771	WF4+75	3.6	2.75"
MON56X	1370772	WF6+80	4.9	3.11"
MON78X	1370773	WF8+150	5.6	3.38"

AUTOMATIC

THE SMART

- Aluminum alloy frame and spool
- Stainless steel main spring
- Main spring release and fold down trigger for easy storage



Model #	SAP #	Reel Size	Weight (oz)
1195X	1149988	7/8	11.2
1195B	1149987	7/8	13.4

MEDALIST

TRADE MARK

EAGLE.



CORK
HANDLE

Classic Fenwick
Actions

5 Year
Limited
WARRANTY



Machined Aluminum
High grade, precision machined
frame and spool



Standard Arbor
High backing capacity spool



Click & Pawl
Precision click check mechanism



Model	SAP	Length	Pieces	Action	Reel	Line Wt	Handle
EAGMEDC804-4	1370760	8'	4	Medium Fast	3/4	4wt	RHW
EAGMEDC905-4	1370761	9'	4	Medium Fast	5/6	5wt	RHW
EAGMEDC908-4	1370762	9'	4	Medium Fast	7/8	8wt	FW+EH

Monarch™



CORK
HANDLE

Classic Fenwick
Actions

5 Year
Limited
WARRANTY

NIGHTHAWK™



Die Cast Aluminum
Lightweight, cast aluminum for
strength and durability



Standard Arbor
High backing capacity spool



Disk Drag
Smooth stacked disk drag
mechanism



Model	SAP	Length	Pieces	Action	Reel	Line Wt	Handle
NM703-4CB0	1370754	7'	4	Medium Fast	3/4	3wt	RHW
NM804-4CB0	1370755	8'	4	Medium Fast	3/4	4wt	RHW
NM905-4CB0	1370756	9'	4	Medium Fast	5/6	5wt	RHW
NM906-4CB0	1370757	9'	4	Medium Fast	5/6	6wt	RHW
NM908-4CB0	1370758	9'	4	Medium Fast	7/8	8wt	FW+EH
NM968-4CB0	1370759	9'6"	4	Medium Fast	7/8	8wt	FW+EH





2017 NA PFLUEGER CATALOG



0 43388 42827 1

1416201

Pure Fishing, inc • Columbia, SC